

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 October 2002 (10.10.2002)

PCT

(10) International Publication Number
WO 02/079353 A1

- (51) International Patent Classification?: C10L 1/14, 10/02, 10/04
- (21) International Application Number: PCT/US02/08509
- (22) International Filing Date: 19 March 2002 (19.03.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/820,430 29 March 2001 (29.03.2001) US
- (71) Applicant: **THE LUBRIZOL CORPORATION**
[US/US]; 29400 Lakeland Boulevard, Wickliffe, OH 44092 (US).
- (72) Inventors: **JACKSON, Mitchell, M.**; 323 Whitetail Drive, Chagrin Falls, OH 44022 (US). **CORKWELL, Keith, C.**; 14351 Chagrin Woods Drive, Newbury, OH 44065 (US).
- (74) Agents: **MUNSON, Jeffrey, F.** et al.; The Lubrizol Corporation, Patent Dept.-022B, 29400 Lakeland Blvd., Wickliffe, OH 44092 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- Published:**
— with international search report
— entirely in electronic form (except for this front page) and available upon request from the International Bureau
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: GASOLINE ADDITIVE CONCENTRATE COMPOSITION AND FUEL COMPOSITION AND METHOD THEREOF

(57) Abstract: A gasoline additive concentrate composition comprises a solvent, an alkoxyated fatty amine, and a partial ester having at least one free hydroxyl group and formed by reacting at least one fatty carboxylic acid and at least one polyhydric alcohol. A fuel composition comprises gasoline and the gasoline additive concentrate composition. A method of operating a gasoline internal combustion engine comprises fueling the engine with the fuel composition and is effective in reducing fuel consumption.



WO 02/079353 A1

TITLE: GASOLINE ADDITIVE CONCENTRATE COMPOSITION
AND FUEL COMPOSITION AND METHOD THEREOF

5

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention involves a gasoline additive concentrate composition, a fuel
composition that includes the gasoline additive concentrate composition, and a
method of operating a gasoline internal combustion engine with the fuel
composition. The compositions and methods of the present invention reduce fuel
consumption in a gasoline internal combustion engine.

2. Description of the Related Art

Gasoline fuel compositions that reduce the fuel consumption of internal
combustion engines are both beneficial and desirable to reduce fuel costs and to
comply with governmental regulations concerning fuel economy and exhaust
emissions.

U.S. Application Serial No. 09/448,560 filed November 23, 1999 (Adams et
al.) disclose compositions that include a polyetheramine and compounds selected
from the group that includes fatty acid esters and alkoxyated amines that are useful
as fuel additives for reducing engine wear and improving fuel economy.

International Application No. WO 93/21288 published October 28, 1993
(Bloch et al.) disclose lubricating oils, such as engine oils and transmission fluids,
that include an alkoxyated amine and an ester of a fatty acid which provide
enhanced fuel economy.

U.S. Patent No. 5,968,211 filed May 26, 1998 (Schilowitz) discloses
gasoline lubricity additive concentrates that include esters of fatty acids and
alkoxyated amines.

European Publication No. EP 947576 published October 6, 1999 (Fuentes-
Afflick et al.) disclose fuel compositions that include aliphatic hydrocarbyl
substituted amines and/or polyetheramines and esters of carboxylic acids and
polyhydric alcohols to improve fuel economy.

U.S. Patent No. 4,617,026 filed August 15, 1984 (Shaub et al.) disclose a method to reduce fuel consumption in a gasoline engine by including a fuel additive that is an ester having at least one free hydroxyl group and formed from a monocarboxylic acid and a glycol or trihydric alcohol.

5 U.S. Patent No. 5,833,722 filed August 9, 1996 (Davies et al.) disclose fuel compositions that include a fuel oil having a low sulfur content, a nitrogen containing compound such as the salt of an amine and carboxylic acid, and an ester of a polyhydric alcohol and a carboxylic acid to enhance lubricity of the fuel.

10 It has now been found that the gasoline additive concentrate composition of the present invention when used in a fuel composition provides a way to reduce fuel consumption in gasoline internal combustion engines. The benefits of this invention are both economic and environmental and include reduced fuel costs, fuel conservation, and reduced emission of greenhouse gases.

SUMMARY OF THE INVENTION

15 It is an object of the present invention to increase fuel economy, reduce fuel consumption, and reduce combustion emissions in gasoline internal combustion engines.

It is a further object of the present invention to decrease engine wear in gasoline internal combustion engines.

20 The objects, advantages and embodiments of the present invention are in part described in the specification and in part are obvious from the specification or from the practice of this invention. Therefore, it is understood that the invention is claimed as described or obvious as falls within the scope of the appended claims.

25 To achieve the foregoing objects in accordance with the invention as described and claimed herein, a gasoline additive concentrate composition of this invention comprises a solvent and an alkoxylated fatty amine, and a partial ester having at least one free hydroxyl group and formed by reacting at least one fatty carboxylic acid and at least one polyhydric alcohol.

30 In another embodiment of the present invention, the gasoline additive concentrate composition further comprises a pour point depressant.

In an additional embodiment of this invention, the gasoline additive concentrate composition further comprises a nitrogen-containing detergent selected

from the group consisting of a polyetheramine, an aliphatic hydrocarbon-substituted amine, a Mannich reaction product formed by reacting an aliphatic hydrocarbon-substituted phenol and an aldehyde and an amine, and mixtures of two or more thereof.

5 A further embodiment of the present invention is a fuel composition comprising gasoline and the foregoing gasoline additive concentrate composition.

A still further embodiment of this invention is a method of operating a gasoline internal combustion engine comprising fueling the engine with the foregoing fuel composition.

10 DETAILED DESCRIPTION OF THE INVENTION

A gasoline additive concentrate composition of the present invention comprises a solvent, and an alkoxyated fatty amine, and a partial ester having at least one free hydroxyl group and formed by reacting at least one fatty carboxylic acid and at least one polyhydric alcohol.

15 The solvent in the present invention provides for a homogeneous and liquid gasoline additive concentrate composition and for facile transferring and handling of the concentrate composition. The solvent also provides for a homogeneous fuel composition comprising gasoline and the concentrate composition. The solvent is selected from the group consisting of aliphatic hydrocarbons, aromatic
20 hydrocarbons, alcohols, and mixtures of two or more thereof. The solvent generally boils in the range of about 65°C to 235°C.

Aliphatic hydrocarbons include various naphtha and kerosene boiling point fractions that have a majority of aliphatic components.


Aromatic hydrocarbons include benzene, toluene, xylenes and various
25 naphtha and kerosene boiling point fractions that have a majority of aromatic components.

Alcohols are usually aliphatic alcohols having about 2 to 10 carbon atoms and include ethanol, 1-propanol, isopropyl alcohol, 1-butanol, isobutyl alcohol, amyl alcohol, and 2-methyl-1-butanol.

30 The concentrate composition of the present invention is prepared by blending the components at ambient or an elevated temperature up to about 65°C until the composition is homogeneous. The solvent can be present in the concentrate

composition at about 10 to 90% by weight, preferably at about 25 to 85% by weight, and more preferably at about 40 to 80% by weight. Preferred solvents are aromatic hydrocarbons and mixtures of alcohols with aromatic hydrocarbons or kerosenes having some aromatic content that allow the concentrate composition to be a liquid at a temperature from about 0°C to minus 18°C.

The alkoxyated fatty amine of the present invention includes amines represented by the formula



where R is a hydrocarbyl group having about 4 to 30 carbon atoms, A¹ and A² are vicinal alkylene groups, and the sum of x and y is an integer and is at least 1. The hydrocarbyl group is a univalent radical of carbon atoms that is predominantly hydrocarbon in nature, but can have nonhydrocarbon substituent groups and can have heteroatoms. The hydrocarbyl group R can be an alkyl or alkylene group of about 4 to 30 carbon atoms, preferably about 10 to 22 carbon atoms. The vicinal alkylene groups A¹ and A² can be the same or different and include ethylene, propylene and butylene having the carbon to nitrogen and carbon to oxygen bonds on adjacent or neighboring carbon atoms. Examples of alkoxyated fatty amines include diethoxylated tallowamine, diethoxylated oleylamine, diethoxylated stearylamine, and the diethoxylated amine from soybean oil fatty acids. Alkoxyated fatty amines are commercially available from Akzo under the Ethomeen® series.

The partial ester of the present invention has at least one free hydroxyl group and is formed by reacting at least one fatty carboxylic acid and at least one polyhydric alcohol.

The fatty carboxylic acid used to form the partial ester can be saturated or unsaturated aliphatic, can be branched or straight chain, can be a monocarboxylic or polycarboxylic acid, and can be a single acid or mixture of acids. The fatty carboxylic acid can have about 4 to 30 carbon atoms, 8 to 26 carbon atoms in another instance, and 12 to 22 carbon atoms in yet another instance. Saturated and unsaturated monocarboxylic acids are useful and include capric, lauric, myristic,

palmitic, stearic, behenic, oleic, petroselinic, elaidic, palmitoleic, linoleic, linolenic and erucic acid.

The polyhydric alcohol used to form the partial ester has two or more hydroxyl groups and includes alkylene glycols, polyalkylene glycols, triols, polyols
5 having more than three hydroxyl groups, and mixtures thereof. Examples of polyhydric alcohols include ethylene glycol, diethylene glycol, neopentyl glycol, glycerol, trimethylol propane, pentaerythritol, and sorbitol.

The partial esters of the present invention, having at least one free hydroxyl group, are commercially available or can be formed by a variety of methods well
10 known in the art. These esters are derived from any of the above described fatty carboxylic acids and polyhydric alcohols or mixtures thereof. Preferred esters are derived from fatty carboxylic acids having about 12 to 22 carbon atoms and glycerol, and will usually be mixtures of mono- and diglycerides. A preferred partial ester is a mixture of glycerol monooleate and glycerol dioleate.

The gasoline additive concentrate composition of this invention further
15 comprises a polymeric pour point depressant. The pour point depressant can further enhance the fluidity, homogeneity, transferring and handling of the concentrate composition especially at a temperature from about 0°C to minus 18°C. Polymeric pour point depressants include polymethacrylates, polyacrylates, esterified
20 copolymers of maleic anhydride and styrene, copolymers of ethylene and vinyl acetate, and terpolymers of dialkyl fumarates with vinyl esters and vinyl ethers. A preferred pour point depressant is the terpolymer prepared from a di(C₁₂₋₁₄ alkyl) fumarate, vinyl acetate and vinyl ethyl ether as described in U.S. Patent 3,250,715. The pour point depressant can be present in the concentrate composition at about
25 0.0001% to 15% by weight, at about 0.001% to 10% by weight in another instance, and at about 0.01% to 10% by weight in yet another instance.

The gasoline additive concentrate composition of the present invention further comprises a nitrogen-containing detergent selected from the group consisting of a polyetheramine, an aliphatic hydrocarbon-substituted amine, and a Mannich
30 reaction product formed by reacting an aliphatic hydrocarbon-substituted phenol and aldehyde and an amine, and mixtures of two or more thereof.

The polyetheramines of the present invention can be represented by the formula $R[OCH_2CH(R^1)]_nA$ where R is a hydrocarbyl group as described above for alkoxyated fatty amines; R^1 is selected from the group consisting of hydrogen, hydrocarbyl groups of 1 to 16 carbon atoms, and mixtures thereof; n is a number
5 from 2 to about 50; and A is selected from the group consisting of $-OCH_2CH_2CH_2NR^2R^2$ and $-NR^3R^3$ where each R^2 is independently hydrogen or hydrocarbyl, and each R^3 is independently hydrogen, hydrocarbyl or $-[R^4N(R^5)]_pR^6$ where R^4 is C_2 - C_{10} alkylene, R^5 and R^6 are independently hydrogen or hydrocarbyl, and p is a number from 1-7.

10 Polyetheramines can be prepared by initially condensing an alcohol or alkylphenol with an alkylene oxide, mixture of alkylene oxides, or several alkylene oxides in sequential fashion in a ratio of about 1 mole of alcohol or alkylphenol to 2-50 moles of alkylene oxide to form a polyether intermediate as described in U.S. Patent 5,094,667. The polyether intermediate can be converted to a polyetheramine
15 by amination with ammonia, an amine or a polyamine as described in published Patent Application EP 310875. In a preferred route, the polyalkoxyated alcohol or alkylphenol is reacted with acrylonitrile and the resultant nitrile is hydrogenated to form a polyetheramine as described in U.S. Patent 5,094,667.

The aliphatic hydrocarbon-substituted amine of this invention can be derived
20 from a polyolefin having a number average molecular weight of about 500 to 5,000, preferably about 700 to 2,300, and more preferably about 750 to 1,500. A preferred polyolefin is polyisobutylene. The aliphatic hydrocarbon-substituted amine can be prepared by methods known in the art to include chlorinating a polyolefin and then reacting the chlorinated polyolefin with an amine or alkanolamine in the presence of
25 a base such as sodium carbonate as described in U.S. Patent 5,407,453. The amine can be a polyamine to include alkylene polyamines such as ethylenediamine and polyalkylene polyamines such as diethylenetriamine. The alkanolamine can be a polyamine such as aminoethylethanolamine.

The Mannich reaction product of the present invention is derived from an
30 aliphatic hydrocarbon-substituted phenol, an aldehyde, and an amine.

The aliphatic hydrocarbon substituent on the phenol can be derived from a polyolefin having a number average molecular weight of about 500 to 3,000,

preferably about 700 to 2,300, and more preferably about 700 to 1,500. A preferred polyolefin is polyisobutylene. A more preferred polyolefin is highly reactive polyisobutylene containing at least 70% of its olefinic double bonds as the vinylidene type at a terminal position on the carbon chain. The aliphatic hydrocarbon-substituted phenol can be prepared by methods well known in the art to include alkylating phenol with a polyolefin using an acidic alkylation catalyst such as boron trifluoride.

The aldehyde used for the Mannich reaction product can be a C₁-C₆ aldehyde. Formaldehyde is preferred and can be used in one of its reagent forms such as paraformaldehyde and formalin.

The amine used for the Mannich reaction product can be a monoamine, polyamine or any organic compound containing at least one >NH group that is capable of undergoing the Mannich reaction. Polyamines include alkylene polyamines such as ethylenediamine and dimethylaminopropylamine and polyalkylene polyamines such as diethylenetriamine.

The Mannich reaction products can be prepared by methods known in the art including those described in U.S. Patents 3,877,889 and 5,697,988 and 5,876,468.

The fuel composition of the present invention comprises gasoline and a gasoline additive concentrate composition. The fuel composition is usually prepared by adding the gasoline additive concentrate composition to the gasoline and mixing them at ambient or an elevated temperature up to about 65°C until the fuel composition is homogeneous.

The gasoline of the present invention is usually a hydrocarbon fuel. The hydrocarbon fuel is typically a liquid fuel, normally a hydrocarbonaceous petroleum distillate fuel such as motor gasoline as defined by ASTM specification D86-00 for a mixture of hydrocarbons having a distillation range from about 60°C at the 10% distillation point to about 205°C at the 90% distillation point. Liquid fuel compositions comprising non-hydrocarbonaceous materials such as alcohols, ethers, organo-nitro compounds and the like (e.g., methanol, ethanol, diethyl ether, methyl ethyl ether, methyl t-butyl ether, nitromethane) are also within the scope of this invention as are liquid fuels derived from vegetable or mineral sources such as corn, alfalfa, shale and coal. Liquid fuels that are mixtures of one or more

hydrocarbonaceous fuels and one or more non-hydrocarbonaceous materials are also contemplated. An example of such mixtures is the combination of gasoline and ethanol.

The gasoline additive concentrate composition used in the fuel composition
5 comprises a solvent, an alkoxyated fatty amine, and a partial ester having at least one free hydroxyl group and formed by reacting at least one fatty carboxylic acid and at least one polyhydric alcohol. In another instance the concentrate composition used in the fuel composition further comprises a polymeric pour point depressant. In yet another instance the concentrate composition used in the fuel composition
10 further comprises a nitrogen-containing detergent selected from the group consisting of a polyetheramine, an aliphatic hydrocarbon-substituted amine, a Mannich reaction product formed by reacting an aliphatic hydrocarbon-substituted phenol and an aldehyde and an amine, and mixtures of two or more thereof. Each of the gasoline additive concentrate composition components to include the alkoxyated fatty amine,
15 partial ester and nitrogen-containing detergent can be present in the fuel composition on a weight basis at about 10 to 2,000 ppm, preferably at about 20 to 1,000 ppm, and more preferably at about 35 to 250 ppm.

The gasoline additive concentrate compositions and fuel compositions of the present invention can contain other additives that are well known to those of skill in
20 the art. These can include anti-knock agents such as tetra-alkyl lead compounds and MMT (methylcyclopentadienyl manganese tricarbonyl), lead scavengers such as halo-alkanes, dyes, antioxidants such as hindered phenols, rust inhibitors such as alkylated succinic acids and anhydrides and derivatives thereof, bacteriostatic agents, auxiliary dispersants and detergents, gum inhibitors, metal deactivators,
25 demulsifiers, anti-valve seat recession additives such as alkali metal sulphosuccinate salts, anti-icing agents, and fluidizer or carrier oils to include mineral oils, polyolefins, polyethers and polyetheramines. The fuel compositions of this invention can be lead-containing or lead-free fuels. Preferred are lead-free fuels.

A method of operating a gasoline internal combustion engine of this
30 invention comprises fueling the engine with a fuel composition comprising gasoline and a gasoline additive concentrate composition comprising a solvent, an alkoxyated fatty amine, and a partial ester having at least one free hydroxyl group

and formed by reacting at least one fatty carboxylic acid and at least one polyhydric alcohol. Additional embodiments of this method of operating the engine include the concentrate composition further comprising pour point depressants or nitrogen-containing detergents as described earlier herein. In still further embodiments of this invention a method of reducing the fuel consumption of a gasoline internal combustion engine comprises fueling the engine with a fuel composition comprising gasoline and a gasoline additive concentrate composition to include the above-described concentrate compositions.

The following examples in Tables 1-3 are for illustrative purposes and show the effectiveness of the concentrate compositions, fuel compositions and methods of the present invention in reducing fuel consumption in gasoline internal combustion engines. Reduction in engine wear is also indicated by the coefficient of friction performance of the present invention.

Table 1

Sequence VIB Dynamometer Test ¹		
Example	Stage 1 Fuel Economy Change ⁴	Stage 2 Fuel Economy Change ⁴
1 (GMO + amine) ²	+0.30%	+0.58%
2 (GMO + amine + Detergents) ³	+2.69%	+1.52%

¹ASTM Sequence VIB Fuel Economy Test: was run using

a) fuel injected 1993 Ford 4.6l engine under standard test parameters specified for stages 1 and 2 of the ASTM test after a 16 hour aging of engine oil,

b) gasoline reference fuel with additives as indicated and without additives for baseline, and

c) SAE 5W30 SJ/GF-2 engine oil.

²Example 1: fuel, 125 ppm by wt. glycerol monooleate (GMO) and 125 ppm by wt. diethoxylated tallowamine (amine).

³Example 3: fuel, 125 ppm by wt. glycerol monooleate (GMO) and 125 ppm by wt. diethoxylated tallowamine (amine), 116 ppm by wt. Mannich reaction product (detergent, from 1,000 mol. wt. polyisobutylene alkylated phenol, formaldehyde and ethylenediamine), and 78 ppm by wt. polyetheramine (detergent, from C₁₂₋₁₅ linear alcohol reacted with 20-24 moles of propylene oxide followed by reaction with acrylonitrile then hydrogenation).

⁴The percent change in fuel economy was determined by comparing fuel consumption based on miles per gallon data of Examples 1 and 2 to a baseline of the reference fuel without additives.

Table 2

Federal Procedure Dynamometer Test ¹	
Example	Fuel Economy Change ⁴
3 (250 ppm of GMO + amine) ²	+1.6%
4 (150 ppm of GMO + amine) ³	+0.9% ⁵

¹U.S. Federal Test Procedure FTP-75: was run using a Ford Crown Victoria 4.6l V8 gasoline engine on a chassis dynamometer under controlled temperature and humidity for the highway portion of FTP-75 in triplicate for each test.

²Example 3: reference fuel, 125 ppm by wt. glycerol monooleate (GMO), and 125 by wt. ppm diethoxylated tallowamine (amine).

³Example 4: reference fuel, 75 ppm by wt. glycerol monooleate (GMO), and 75 ppm by wt. diethoxylated tallowamine (amine).

⁴The percent change in fuel economy was determined by comparing fuel consumption based on miles per gallon data of Examples 3 and 4 to a baseline of the reference fuel without additives.

⁵The fuel economy change was based on the results of tests run twice for Example 4 and for the baseline.

Table 3

SRV (Oscillating Friction Wear) Test ¹			
Example	Composition ²	Coefficient of Friction	Reduction in Coefficient of Friction ³
5	oil	0.166	-
6	oil + 1% GMO	0.129	22.3%
7	oil + 0.5% GMO + 0.5% amine	0.123	25.9%
8	oil + 0.5% GMO	0.134	19.3%
9	oil + 0.25% GMO + 0.25% amine	0.124	25.3%
10	oil + 0.25% GMO	0.145	12.7%
11	oil + 0.125% GMO + 0.125% amine	0.139	16.3%

¹SRV (Oscillating Friction Wear) Test: the SRV test device run under a 75N load at 50 Hz with a 1.5mm stroke and a temperature ramp to 120°C.

²The Examples contain 180 neutral oil and as indicated in weight percent glycerol monooleate (GMO) and diethoxylated tallowamine (amine).

³The percent reduction in the coefficient of friction is relative to the oil baseline of Example 5.

What is claimed is:

5

1. A gasoline additive concentrate composition, comprising:

a solvent; and

an alkoxyated fatty amine; and


10 a partial ester having at least one free hydroxyl group and formed by reacting at least one fatty carboxylic acid and at least one polyhydric alcohol.

2. The composition of claim 1 wherein the solvent is selected from the group consisting of aliphatic hydrocarbons, aromatic hydrocarbons, alcohols, and mixtures of two or more thereof.

15

3. The composition of claim 1 wherein the concentrate composition is a liquid at a temperature from about 0°C to minus 18°C.

20 4. The composition of claim 1 wherein the alkoxyated fatty amine is represented by the formula



wherein R is a hydrocarbyl group having about 4 to 30 carbon atoms, A¹ and A² are vicinal alkylene groups, and the sum of x and y is at least 1.

25 5. The composition of claim 4 wherein the alkoxyated fatty amine is a diethoxylated fatty amine having about 16 to 18 carbon atoms.

6. The composition of claim 1 wherein the fatty carboxylic acid has about 4 to 30 carbon atoms.

30

7. The composition of claim 1 wherein the fatty carboxylic acid is a saturated aliphatic monocarboxylic acid or an unsaturated aliphatic monocarboxylic acid.
8. The composition of claim 1 wherein the fatty carboxylic acid is oleic acid.
- 5 9. The composition of claim 1 wherein the polyhydric alcohol is glycerol or ethylene glycol.
- 10 10. The composition of claim 1 wherein the partial ester is a mixture of glycerol monooleate and glycerol dioleate.
11. The composition of claim 1 further comprising a polymeric pour point depressant.
- 15 12. The composition of claim 11 wherein the polymeric pour point depressant is a terpolymer formed by polymerizing a dialkyl fumarate, a vinyl carboxylate, and a vinyl ether.
- 20 13. The composition of claim 1 further comprising a nitrogen-containing detergent selected from the group consisting of a polyetheramine, an aliphatic hydrocarbon-substituted amine, a Mannich reaction product formed by reacting an aliphatic hydrocarbon-substituted phenol and an aldehyde and an amine, and mixtures of two or more thereof.
- 25 14. The composition of claim 13 wherein the polyetheramine is formed by hydrogenating a nitrile which is prepared by reacting a polyalkoxylated alcohol or alkylphenol and acrylonitrile.
- 30 15. A fuel composition, comprising:
gasoline; and
the gasoline additive concentrate composition of claim 1.

16. A fuel composition, comprising:
gasoline; and
the gasoline additive concentrate composition of claim 11.
- 5 17. A fuel composition, comprising:
gasoline; and
the gasoline additive concentrate composition of claim 13.
18. A method of operating a gasoline internal combustion engine comprising
10 fueling the engine with the fuel composition of claim 15.
19. A method of reducing the fuel consumption of a gasoline internal combustion
engine comprising fueling the engine with the fuel composition of claim 15.

INTERNATIONAL SEARCH REPORT

Inte al Application No

PCT/US 02/08509

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C10L1/14 C10L10/02 C10L10/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C10L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 93 21288 A (EXXON CHEMICAL PATENTS INC) 28 October 1993 (1993-10-28) cited in the application examples 3,6	1-19
Y	EP 0 869 163 A (MOBIL OIL CORP) 7 October 1998 (1998-10-07) page 6, line 21 -page 6, line 45; claim 1	1-19
Y	EP 0 227 218 A (EXXON RESEARCH ENGINEERING CO) 1 July 1987 (1987-07-01) example 1	1-19
Y	US 5 968 211 A (SCHILOWITZ ALAN M) 19 October 1999 (1999-10-19) cited in the application column 1, line 51 -column 2, line 8; table 4	1-3
-/--		

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

11 June 2002

Date of mailing of the international search report

24/06/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Keipert, O

INTERNATIONAL SEARCH REPORT

Inter ☐ International Application No

PCT/US 02/08509

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 3 250 715 A (WYMAN DONALD P) 10 May 1966 (1966-05-10) cited in the application the whole document ----	1,11,12, 15,16, 18,19
Y	US 5 094 667 A (SCHILOWITZ ALAN M ET AL) 10 March 1992 (1992-03-10) cited in the application the whole document ----	1,13,14, 17
A	EP 0 957 152 A (KAO CORP) 17 November 1999 (1999-11-17) page 13, line 35 -page 13, line 52 -----	

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9321288	A	28-10-1993	AU 4048793 A CA 2131098 A1 EP 0649459 A1 JP 7508771 T MX 9302129 A1 WO 9321288 A1	18-11-1993 16-10-1993 26-04-1995 28-09-1995 30-06-1994 28-10-1993
EP 0869163	A	07-10-1998	EP 0869163 A1	07-10-1998
EP 0227218	A	01-07-1987	EP 0227218 A1 JP 62148595 A	01-07-1987 02-07-1987
US 5968211	A	19-10-1999	AT 202595 T DE 69613549 D1 DE 69613549 T2 EP 0780460 A1	15-07-2001 02-08-2001 25-10-2001 25-06-1997
US 3250715	A	10-05-1966	FR 1451251 A GB 1059878 A	07-12-1966 22-02-1967
US 5094667	A	10-03-1992	CA 2038627 A1 EP 0448365 A1 FI 911338 A JP 7070008 A NO 911067 A US 5264006 A	21-09-1991 25-09-1991 21-09-1991 14-03-1995 23-09-1991 23-11-1993
EP 0957152	A	17-11-1999	EP 0957152 A1 WO 9727271 A1	17-11-1999 31-07-1997